



ConduRod Technical Specifications

Physical Properties

Property	Typical Value	Unit	Test Method
Physical State	Black Solid		
Odor	None		
Water Permeability	1.72×10^{-7}	cm/sec	ASTM D5084 (2.6 psi)
Flammability	No ignition		Exposed to a propane torch (~2000 °C) for 60 seconds
Electrical Corrosion Resistance Copper Steel Galvanized Steel	100 98.09 99.91	%	SAE Inc. Standard 100
Compatibility Copper Steel Galvanized Steel	Yes Yes Yes		SAE Inc. Standard 100
Environmental Impact	Neutral		Ontario Regulation 558/00 (Leachate Testing)
Freeze-thaw Withstand	30	Years	SAE Inc. Standard 102

Electrical Properties

Property	Typical Value	Unit	Test Method
Resistance	0.031	Ω	SAE Inc. Standard 105
Resistivity	30.39	$\Omega \cdot \text{cm}$	SAE Inc. Standard 105

Leachate (TCLP) Results

Leachate Data (TCLP Procedure) based on Ontario Regulation 558/00

Constituent	ConduRod TCLP Concentration (mg/L)	USEPA Maximum Contaminant Level (mg/L)
Arsenic	BDL	0.010
Barium	1.490	2.000
Boron	1.067	2.000 *
Chromium	0.026	0.100
Mercury	BDL	0.002
Selenium	0.013	0.050
Silver	BDL	0.100 **
Uranium	BDL	0.030
Fluoride	0.190	2.000 **
Nitrate (as Nitrogen)	BDL	10.000
Nitrite (as Nitrogen)	BDL	1.000
Cyanide	BDL	0.200

BDL means the result is "Below the Detection Level" of the analytical procedure

* No MCL established; value shown is USEPA's Lifetime Drinking Water Health Advisory

** No MCL established; value shown is USEPA's Secondary Drinking Water Standard

Published Date: September 2022